pilotair
The Compressed Air Experts

NGS-15VS

Variable Speed Rotary Screw Compressor



Industrial Performance. Intelligent Efficiency.
Engineered for Reliability.

NGS-15VS Key Benefits

Energy-efficient airend

Premium IE3 motor

Advanced controller

Low noise operation

Heavy-duty build quality

3 year warranty











Technical Specifications

No.	Item		Unit	Parameter
1	Air flow/Working Pressure		(L/S) / BAR	35 / 10
2	Ambient temperature		℃	-5～+45
3	Cooling method			Air-cooling
4	Exhaust temperature		℃	≤Ambient temperature+15
5	Lubricating oil quantity		L	10
6	Transmission method			Direct
7	Gas flow control method			Loading/unloading
8	Gas oil content		ppm	≤3
9	Noise		dB(A)	72±2
10	Lubricant Type			46 grade mineral oil
11	Safety valve set pressure		MPa	Rated working pressurex1.1
12	Motor	Power	kW	15
		Speed	rpm	2930
		Starting Method		Inverted
		Voltage/Frequency	V/Hz	415/50
		Protection Level/Insulatior		IP55, Grade F
12	Fan	Power	kW	0.25
		Voltage/Frequency	V/Hz	415/50
		Speed	rpm	1440
		Air Volume	m3/h	4000
14	Dimensions		mm	1160*700*1100
15	Weight		kg	230
16	Outlet pipe diameter		in	G 3/4

pilotair
The Compressed Air Experts

Contact Us for pricing & availability

NSW

Head Office & Manufacturing
115 Beaconsfield Street,
Silverwater, Sydney NSW 2128

Service and Spares Division
21-25 Stubbs Street,
Auburn, Sydney NSW 2144

VIC Branch	1300 667 579
QLD Branch	07 3279 1213
WA Branch	08 9424 2800
SA Branch	1300 667 579
Website	www.pilotair.com.au
Email	sales.pilotair.com.au

SUBMIT AN ENQUIRY

